

## MINERAL CORE 45MIN-60 FIRE RATING

WDFR\_45N\_MIN | WDFR\_45B\_MIN | WDFR\_45A\_MIN | WDFR\_60N\_MIN | WDFR\_60B\_MIN | WDFR\_60A\_MIN  
 Architectural Series



	SERIES	ARCHITECTURAL
FIRE RATING	Label	Warnock Hershey - Intertek per NFPA 80 4.2
	Pressure	Neutral, Cat A Positive, Cat B Positive
DIMENSIONS	Thickness	1-3/4", 2", 2 1/4" (+- 1/16")
	Maximum Sizes	For Max Sizes, please review WKS Door Systems Fire Rating Chart
CONSTRUCTION	Ply	5 PLY BONDED
	Core	Mineral Fire-Resistance Composite per Label Listing
	Vertical Edges	1 1/2" FR Stiles Stiles with Matching Wood Veneer/ HPDL Edgeband Over or Finished Mill Option Primed or Painted Edge, Standard Bevel 1/8" in 2"
	Horizontal Edges	2" FR Rails with surface applied intumescent (PP CAT A), 5" FR Rails Reinforcement, sealed top & bottom rails upon request
	Blocking	Multiple Reinforcement locations available upon request, consult with your ISR
	Crossband	One Piece High Density Fiberboard (HDF)
	Veneer Grade/ Species	"A" & "AA"/ Premium, Custom per ANSI/WDMA I.S.1A
	Veneer Match/ Assembly	<ul style="list-style-type: none"> <li>• Book Match Standard, Slip or Random available</li> <li>• Running Match Standard, Center, Balanced or Center Balanced available</li> </ul>
	Grain Orientation	Vertical, Horizontal, Mixed and Sketch Face
	Factory Finish	WDMA TR-8 / AWS SYSTEM 9, UV Cured Acrylated - Polyurethane: Clear, Light, Dark and Custom Stain colors.
	Laminated Surface	High Pressure Decorative Laminate NEMA LD3-2005, Wood Grains, Solid Colors and Patterns
	Paint Grade	One Piece High Density Fiberboard (HDF)
	Factory Finish	Primed Factory Finish or Solid Colors
Adhesive/ Weight	Type 2/ 30.77 kg/mt2 - 6.30 lb/ft2	
ELEVATIONS	Vision Lites	Min Distances: Top Rail: 6", Bottom Rail: 10", Stiles: 6" 5" min of core material between the lockset prep and cutout Light cutout may not exceed 1,232 Sq.In. area, or 36" width, or 54" height Metal Vision Frames only (wood mouldings not allowed)
	Reveals	Allowed with restrictions, consult with your ISR
	Louvers	Min Distances: Bottom Rail: 10", Stiles: 6" Light cutout may not exceed 524 Sq.In. area, or 24" width, or 24" height Metal Fusible Link only (cutout only), wood louvers not allowed
STC	Sound Rating	30 STC with installed seals and gaskets tested Automatic Bottom Seal is recommended by WKS for a high performance
QUALITY STANDARDS	Environmental	FSC Credit MR7 available upon request CARB Phase 2 / TSCA VI Compliant
	Performance	Heavy, Extra Heavy Duty per WDMA I.S.1A Architectural Wood Flush Doors
	Warranty	Interior Use Only (no exterior warranty). Lifetime; life of original installation
	Machining	Hardware preps shall be factory machined from manufacturer's templates and shop drawings

*Fire Rated Doors are manufactured per the standards listed on this page. Specifications are subject to the label listing and may change without notice. To ensure please contact your WKS Door Systems representative.*

