

STRUCTURAL COMPOSITE CORE 20 MIN-FIRE RATING & NON RATED

WDNR_SCL | WDFR_20N_SCL | WDFR_20B_SCL | WDFR_20A_SCL

Architectural Series



	SERIES	ARCHITECTURAL
FIRE RATING	Label	Warnock Hershey - Intertek per NFPA 80 4.2
	Pressure	Neutral, Cat A Positive, Cat B Positive
DIMENSIONS	Thickness	1-3/4", 2", 2 1/4" (+- 1/16")
	Maximum Sizes	For Max Sizes, please review WKS Door Systems Fire Rating Chart
CONSTRUCTION	Ply	5 PLY BONDED/ NO BONDED
	Core	Structural Composite Lumber per Label Listing
	Vertical Edges	1 5/16" SCL Stiles with Matching Wood Veneer/ HPDL Edgeband Over or Finished Mill Option Primed or Painted Edge, Standard Bevel 1/8" in 2"
	Horizontal Edges	1 5/16" SCL Top & Bottom Rails (5" Rails Reinforcement, Sealed Top & Bottom Rails upon request)
	Crossband	One Piece High Density Fiberboard (HDF)
	Veneer Grade/ Species	"A" & "AA" / Premium, Custom per ANSI/WDMA I.S.1A
	Veneer Match/ Assembly	• Book Match Standard, Slip or Random available • Running Match Standard, Center, Balanced or Center Balanced available
	Grain Orientation	Vertical, Horizontal, Mixed and Sketch Face
	Factory Finish	WDMA TR-8 / AWS SYSTEM 9, UV Cured Acrylated - Polyurethane: Clear, Light, Dark and Custom Stain colors
	Laminated Surface	High Pressure Decorative Laminate NEMA LD3-2005, Wood Grains, Solid Colors and Patterns
	Paint Grade	One Piece High Density Fiberboard (HDF)
	Factory Finish	Primed Factory Finish or Solid Colors
	Adhesive/ Weight	Type 2/ 29 kg/mt2 - 5.94 lb/ ft2
ELEVATIONS	Vision Lites	Min Distances: Top Rail: 6", Bottom Rail: 10", Stiles: 6" 3.25" min of core material between the lockset prep and cutout Light cutout Non Rated: 2,880 Sq.In. area, or 36" width, or 80" height may not exceed: Fire Rated: 2,560 Sq.In. area, or 32" width, or 80" height Non Rated: Metal Vision Frame (cutout only) Fire Rated: Metal Vision Frame
	Reveals	Allowed with restrictions, consult with your ISR Min Distances: Top Rail: 6", Bottom Rail: 10", Stiles: 6"
	Louvers	Light cutout may not exceed 2,880 Sq.In. area, or 36" width, or 80" height Non Rated: Wood and Metal available Fire Rated: Not Allowed
STC	Sound Rating	30 STC with installed seals and gaskets tested Automatic Bottom Seal is recommended by WKS for a high performance
QUALITY STANDARDS	Environmental	FSC Credit MR7 available upon request CARB Phase 2 / TSCA VI Compliant
	Performance	Heavy, Extra Heavy Duty per WDMA I.S.1A Architectural Wood Flush Doors
	Warranty	Interior Use Only (no exterior warranty). Lifetime; life of original installation
	Machining	Hardware preps shall be factory machined from manufacturer's templates and shop drawings

Fire Rated Doors are manufactured per the standards listed on this page. Specifications are subject to the label listing and may change without notice. To ensure please contact your WKS Door Systems representative.

