

TUBULAR CORE 20MIN FIRE RATING & NON RATED
 WDNR_TUB | WDNR_20N-TUB
 Architectural Series



	SERIES	ARCHITECTURAL			
FIRE RATING	Label	Warnock Hershey - Intertek / NFPA Compliance			
	Pressure	Neutral			
DIMENSIONS	Thickness	1-3/4"			
	Maximum Sizes		<i>Neutral</i>	<i>Cat A Positive</i>	<i>Cat B Positive</i>
		Singles (Swing)	4'00" x 10'00"	4'00" x 8'00"	N/A
		Standard Pairs	8'00" x 10'00"	8'00" x 8'00"	N/A
Double Egress Pairs	8'00" x 10'00"	N/A	N/A		
CONSTRUCTION	Ply	5 PLY BONDED/ NO BONDED.			
	Core	Extruded Tubular per Label Listing			
	Vertical Edges	1 5/16" SCL Stiles with Matching Veneer Edgeband Over			
	Horizontal Edges	1 5/16" SCL Rails (5" Rails Reinforcement upon request)			
	Crossband	One Piece High Density Fiberboard (HDF)			
	Veneer Grade/ Species	"A" & "AA" / Standard, Exotic and Engineered			
	Veneer Match/ Assembly	<ul style="list-style-type: none"> • Book Match Standard, Slip or Random available • Running Match Standard, Center, Balanced or Center Balanced available 			
	Grain Orientation	Vertical (standard), Horizontal, Mixed and Sketch Face (upon request)			
	Factory Finish	WDMA TR-8 / AWS SYSTEM 9, UV Cured Acrylated - Polyurethane: Clear, Light, Dark and Custom Stain colors			
	Laminated Surface	High Pressure Decorative Laminate			
	Paint Grade	One Piece High Density Fiberboard (HDF)			
	Factory Finish	UV Cured: Primed, Paint Skin, Standard and Custom Paint colors			
	Adhesive/ Weight	Type 2 / 19 kg/mt2 - 3.89 lb/ft2			
ELEVATIONS	Vision Lites	Not Allowed			
	Reveals	Allowed with restrictions, consult with your ISR			
	Louvers	Not Allowed			
STC	Sound Rating	32 STC with installed seals and gaskets tested Automatic Bottom Seal is recommended by WKS for a high performance			
	Environmental	FSC Certification MR7 and NAUF EQ4.4 Credit available upon request Environmental Product Declaration available upon request			
QUALITY STANDARDS	Performance	BS EN 14755:2005 British Standards Institute (european construction)			
	Warranty	Interior Use Only (no exterior warranty). Lifetime; life of original installation			
	Machining	Hardware preps shall be factory machined from manufacturer' templates and shop drawings. Order will not be procesed without complete information			

Fire Rated Doors are manufactured per the standards listed on this page. Specifications are subject to the label listing and may change without notice. To ensure please contact your WKS Door Systems representative.

